

2024 Bumper swap compacts

General rules/ car preparations

1. Any year car permitted front wheel drive cars only within 110 inch wheelbase
2. Cars Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show all wagons must remove roof racks and decking
3. All glass must be removed and swept clean
4. All batteries must be moved in the drivers compartment (2 battery maximum)
5. Car must have a seat belt and working brakes at all times
6. You will have two times throw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
7. **Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech**
8. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want)
9. All judge's decision are final
10. We reserve the right to drill,scope,unbolt anything we feel could potentially be hiding something
11. Pre ran cars must follow these rules and change what needs to be changed we will not change the rules to fit your car you must change your car to fit our rules

Frames

1. Frames must be 100 percent stock absolutely no welding anywhere will be permitted unless otherwise stated
2. No seam welding even where factory missed
 - If found you will cut the center of weld out with a grinder or torch
3. You may notch or dimple cars in one location
4. UNIBODY CARS STILL HAVE FRAME RAILS, FOLLOW THE FRAME BUILDING RULES.
5. No painting or undercoating of frames
 - If found you will be required to remove
 - Over spray is considered paint and will be removed also
 - No fresh undercoating
6. If frame is rusted we must have proof of rust and must be approved by either matthew kingree or jesse bly

Shorting of frames

1. May shorten frame to front edge of Core support
2. No shorting of rear of vehicles

Repair/fresh plates/9 wire

1. If car is fresh/pre ran you are allowed 4- 4x4" ¼" square plates (2 per rail)
 - Square or parallelogram plates
 - Must have a 1 inch gap between welds
 - ½ weld max around plates

- Welds/plate Must remain 2 inches away from bumper shock
- May have 8 spots of double strand 9 wire from sheet metal to sub/uni body May touch cage
- Plates must be external
- Must be painted orange for easy identification
- Plates are not allowed to tie subframe to uni bodys or k frames to uni bodys

Bumpers

1. Any factory loaded seam welded automobile bumper
2. **Use bumper rules for front and rear of car**
 - we will be allowing a smith metal works or similar bumpers
 - Home made bumpers not to exceed 6x6 tube may have a point must not be no more than 4in away from front face of bumper and must expand 32 inches across the front
 - Rear bumpers must be a minimum of 5 inches on back surface
 - Replicated bumpers will be allowed
 - **No pointy or slanted bumpers on rear of any car**

Bumper mounting

1. You will be allowed a 4 inch wide by 6 inch long bumper bracket/shock (4"x6"x 3/8") or (2"x2") tube
 - Plate can only be on one side of the frame not all 4
 - May contour or remain straight
 - Must touch front bumper and anything past 6 inches will be removed factory or not
 - If you choose to run a factory shock or bracket anything pass the 6 inches will be removed
 - If using the plate options you must remove factory shock/ bracket
2. Bumper brackets and shocks must be factory to car you are running and bumper shocks must be in the factory location
3. May use a 6"x6" 1/4 plate welded to end of frame to make a flat mounting surface must be welded in between the fame and bumper and remain the 6"x6" no folding over plate on to frame
4. Bumpers may be welded on to the end of the frame no sliding bumper over or inside of end of the frame or subframe rails
5. If unable to weld your bumper on you may wire, chain, and bolt your bumper on and may leave the shock this is for the cars that bumper was not welded on
6. You are allowed two spots of double strand 9 wire from bumper to sheet metal only must follow the following
 - On the front bumper 9 wire may only go around core support may not be wrapped through hood or around front all thread mounts
 - Rear bumper 9 wire may only go from bumper to trunk lid must only be to sheet metal

Body

1. No body modifications must be stock unless otherwise stated
2. No changing of body mounts must remain factory zero modifications
3. Creasing is allowed but limited to front fenders and rear quarters

Doors

1. Drivers door may be welded solid and all other doors may be welded with a total of 6 plates 3x5x1/4
 - You will be allowed a inner or outer door plate on drivers side only this is for drivers protection
 - No thicker than 1/4 inch and can only go 3 inches of each door seam
2. If not welded may be chained or wired 8 spots per door
3. you may weld a standard 5/8 washer around holes to prevent ripping
4. Top of doors may be beat down but may not be welded,bolted, or screwed back in place

trunks/tailgates

1. Rear quarters must remain factory height
2. Trunks must remain factory and above rain channels you may do a simple tuck but can not attach to the floor in any way
3. Trunks can be may be chained or wired,welded must pick one of the three options
 - If wired may have 10 spots you may not exceed over two strands of 9 wire thru each spot a 5/8 standard store bought washer may be welded around whole to prevent ripping
 - If chained you may do 8 spots 3/8 links and must remain free floating a 5/8 standard store bought washer may be welded around whole to prevent ripping
 - If welded you may do 6 spots 3x5x1/4 plate may be used

Hoods

1. Hoods must have a minimum 12x12 hole in it for fires can be bolted back together with 4 3/8 bolts with a standard nut and washer
2. hoods must remain open for tech if you come threw tech with it chained or wired down we will not inspect your car
3. hoods may be chained, wired or bolted one of the three may be used
 - If chained or wired you may do 8 spots of wire or chain you may weld a standard 5/8 washer around holes to prevent ripping
 - If bolted you may use 6 spots and you may use 2x2 angle 2 inches long in 6 spots with a standard 1/2 bolt and washer

Window bars

1. You may have one front and rear window bar can only attach to first 6 inches of roof and first 6 inches of cowl panel or trunk lid closest to window
 - If its square tube nothing bigger than 2x2 1/4 pipe
 - 3in wide 3/8 stock bar
 - Chain
 - Or 9 wire
 - One of the following not all of them
 - No rear window bars on wagons

Cage

1. A 4 point cage and halo bar is highly recommend but is optional
 - Cage size may not exceed 2 x 6 ¼ or 4 inches in diameter
2. Cage can not be in the doors
3. All cage material must be 5 inches off floor no exceptions
4. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
 - Side bars must be 62 inches long and must also remain 5 inches away from fire wall and 5 inches from floor
5. May have a center bar must be 5in off all parts of the floor sheet metal
6. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it may be connected to the roof in two spots
 - Attachment points may be 2x2 ¼ 6 inch long angle with a ½ bolt with a standard washer and nut only
7. You can have guessests in corners of the cage
8. 4 inch long max and 1/4inch material

Gas tank protector

1. You will be allowed a 32in wide tank proctor
 - It can not attach to any sheet metal and must stay in front of rear axle
 - You are allowed to build an upper halo around your gas tank protector but can be no higher than 3 inches above tank
 - You may have bars running from tank protector to halo bar
 - **If your tank is under your car you may not have a tank protector**

suspension

1. Must remain stock absolutely no aftermarket or modified parts 100% stock
2. Only aftermarket parts your allowed is spring spacers or the strut risers
3. Cars must have suspension bounce
4. No aftermarket or modified tie rods must remain factory
5. Steering column may be changed to an aftermarket
6. All control arms must be stock and no modifications allowed and must be in factory location of the car you are running
7. No chaining of the rear to set the height

Tires

1. Any tire and wheel combo permitted
2. Must have started as a factory rim
3. May run bead locks, lip proctors, full centers, valve stem protectors

motor/trans

1. Motor and trans must be factory to make and model no switching makes (ford to ford chevy to chevy Toyota to Toyota)
2. You may run an aftermarket motor mounts on front of engine only 2x2 max size

- Toyota products may change the front motor mount running to the k frame must bolt back as factory intended no welding allowed
 - Gm products may change the upper two mounts must bolt in to the factory brackets on both motor and core support
 - Honda products may change the front mount also must be done as factory attend
3. No engine cradles distributor protectors trans braces coil pack protectors no protectors in general must all be oem
 4. Trans must be factory to car and mounted in factory location
 5. Trans coolers are permitted but must be mounted in drivers compartment and must use appropriate lines (hydraulic hoses are highly recommended)
 6. You may run aftermarket shifter
 7. Headers will be allowed
 8. Carb conversions are allowed

Full tanks

1. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure
2. Must be secured and safe if we deem any part of fuel system is unsafe you will fix issues until it's deemed safe
3. **(we all have families that need us this rule is the most important and will be enforced no matter the outcome)**
4. If tank is in front of rear axle it may be left there but must have a skid plate

Aftermarket parts premitted

1. Headers
2. Shifters
3. Pedal combos
4. Steering columns
5. Fuel cells

Nothing else is permitted unless approved by either jesse bly or matthew kingree

For all rule questions please contact jesse bly at (540) 335-0723

2024 chaos in the valley lightweld

General rules/ car preparations

1. Any year car permitted except for the following limos ,checker cabs, trucks, suvs
2. Cars Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show all wagons must remove roof racks and decking
3. All glass must be removed and swept clean
4. Original full tanks must be removed and placed in back seat area
5. All batteries must be moved in the drivers compartment (2 battery maximum)
6. Car must have a seat belt and working brakes at all times
7. You will have two times threw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
8. **Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech**
9. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want if you have read the rules this far and have found this you will be allowed two extra plates please contact us to receive your plates)
10. All judge's decision are final
11. We reserve the right to drill,scope,unbolt anything we feel could potentially be hiding something
12. Pre ran cars must follow these rules and change what needs to be changed we will not change the rules to fit your car you must change your car to fit our rules

Frames

1. Frames must be 100 percent stock absolutely no welding anywhere will be permitted unless otherwise stated
2. No frame shaping
3. Cars may be dimpled on top side of frame in two locations per rear frame rail to help with rear of car to bend up.
4. UNIBODY CARS STILL HAVE FRAME RAILS, FOLLOW THE FRAME BUILDING RULES.
5. Chrysler K-Members cannot be altered.
6. Imperial subs must be in imperials
 - No putting an imperial subframes or k members in any other chrysler products
7. If your car needs a new stub or frame rails you may only replace with same year make and model rails this is for pre runs only and must follow the following guidelines
 - No metal may be added
 - All metal must be butt welded together no overlapping of the materials
 - No weld can be more than ½ wide
 - Must be put back as it would be from factory
8. No painting of frames
 - If found you will be required to remove

- Over spray is considered paint and will be removed also
 - No fresh undercoating
9. No seam welding even where factory missed
 - If found to be welded you will be forced to grind or torch the center out of the weld the whole length
 10. No tilting cold bending or any kind of frame work
 11. You may notch or dimple cars in rear frame rails
 12. Sway bar must be 100% factory on both frame and a arm/ spindle
 - If running a sway bar pulley protector must be removed
 13. 03 and newer ford mercurys and lincoln's must run the factory aluminum cradle see engine mounting rules for motor details

Shorting of frames

1. May shorten frame to front edge of coresupport whole
 - If it is a weld on mount leave the remaining portion of the body mount in place. If you remove the body mount completely or relocate it, you will not run.
 - No seems on mount may be rewelded
 - If your car does not have a weld on mount may only shorten to 1 in infront of factory core support whole
2. Rear of cars may not be shortened

Repair/prior plates/9 wire rules

1. If car is fresh/ pre ran you are allowed 4- 4x4" 1/4" square plates (2 per rail)
 - Square or parallelogram or taco plates
 - Must have a 1 inch gap between welds
 - 1/2 inch weld max around plate
 - Welds/plate Must remain 2 inches away from bumper shock
 - Welds/plate must remain 1in away from a arm strap
 - May have 8 spots of double strand 9 wire from sheet metal to frame May not connect or go around any part of cage
 - Plates must be external
 - Plates Must be painted orange for easy identification
 - Welds must be painted orange where cars are restubed
 - Plates are not allowed to tie any engine cradles/ midplates/ block savers/ transmission crossmember into frames.
 - Behind rear of car You are permitted 1 double strand of #9 wire or May use a standard 3/8 chain must wrap around frame or go through a factory whole no metal may be added to frame

Bumpers

1. Any factory loaded seam welded automobile bumper
2. **Use bumper rules for front and rear of car**
 - we will be allowing a smith metal works or similar bumpers

- Home made bumpers not to exceed 6x6 tube may have a point must not be no more than 4in away from front face of bumper and must expand 32 inches across the front
- Rear bumpers must be a minimum of 5 inches on back surface
- Replicated bumpers will be allowed
- **No pointy or slanted bumpers on rear of any car**

Bumper mounting

1. You will be allowed a 4 inch wide by 8 inch long bumper bracket (4"x8"x 3/8")
 - Plate can only be on one side of the frame not all 4
 - May contour or remain straight
 - Must touch front bumper and anything past 8 inches will be removed factory or not
 - If you choose to run a factory shock or bracket anything pass the 8 inches will be removed
 - If using the plate options you must remove factory shock/ bracket
 - 1/2 wide max bead
2. Bumper brackets and shocks must be factory to car you are running and bumper shocks must be in the factory location
3. May use a 6x6 1/4 plate welded to end of frame to make a flat mounting surface must be welded in between the fame and bumper and remain the 6x6 no folding over plate on to frame
4. Bumpers may be welded on to the end of the frame no sliding bumper over or inside of end of the frame or subframe rails
5. If unable to weld your bumper on you may wire, chain, and bolt your bumper on and may leave the shock this is for the cars that bumper was not welded on
6. You are allowed two spots of double strand 9 wire from bumper to sheet metal only must follow the following
 - On the front bumper 9 wire may only go around core support may not be wrapped through hood or around front all thread mounts
 - Rear bumper 9 wire may only go from bumper to trunk lid must only be to sheet metal

Bumper height restrictions

- Front bumper height is 22 inches to bottom of the bumper
- Rear bumper height is 15 inches to the bottom of the frame around the bumper mounting area.
- All cars will meet bumper height requirements by our inspection area and all cars fresh or pre ran will meet requirement

Body

1. No body modifications must be stock unless otherwise stated
2. All cars must be stripped clean and swept clean
3. Rear decking must be removed from rear of wagons and roof racks must be removed

Body mounts

1. changing of body mounts will be permitted must follow the following guidelines
 - Bolts can not be no bigger than 5/8 in bolts or threaded rod
 - Must stop and begin like factory
 - Washers on inside of frame and body must not be no bigger that 3 in round or square
 - Must have a 1 inch gap with a rubber mount
4. The front two core support mounts may be changed to 1in thread rod and can be ran through the hood but will count as two of your tie down spots and can use no washers bigger than 4x4 ¼ plate or 5in round

Doors

1. Driver door and front passenger door only may be welded solid
2. all other doors May be wired chained or welded one of the three options only
 - if wired 8 spots per vertical door seam can not be wrapped around the frame.
 - If chained, 6 spots per door can not be wrapped around the frame.
 - If welded doors may 3x5 ¼ plate and can only have 3 plates per vertical door seam
 - ❖ If welded In between plates the seems may not be welded
3. Inner and outer door skins are permitted on drivers door only this is for drivers safety may not go past door seem more than 3 inches

Body patching

1. Patching will be limited to floors and roofs must be done with same thickness of metal can only overlap 1in past whole and must prove rust (with a picture prior to the show) all other areas will need to be approved before doing so
2. If car is pre ran you may plate over ripped sheet metal on doors and doors only must use no thicker than ⅛ material

Trunks/ tailgates

1. must remain factory and above rain channels Rear quarters must remain factory height
2. Quarters may be creased but tops must remain in upright position
3. You may roll bottoms of quarters but may not bolt back to body or be in between frame
- 4. If your car is pre ran and your quarters are folded over you must attempt to bring them back up to factory location**
5. may do a simple tuck or dish is allowed
6. No wedged cars allowed (pre ran or fresh)
7. Tucks may not be connected to the floor
8. Dished trunks can not be dished any more than 6 inches measurements will be taken from top of quarters with a straight edge
9. may be weld,wire,and chain not all three
10. if welded must be done with 8 plates total 3x5x ¼ max
11. If running a wagon you will only be allowed 4 plates total to weld your tailgate 3x5x ¼ max

12. If chained or wired you may do 8 spots you may weld a standard $\frac{5}{8}$ washer around holes to prevent ripping
13. Speaker decks must be up and in factory location
14. Wagons will be considered a tailgate no matter what way it opens
15. **If your car is pre ran and your quarters are folded over you must attempt to bring them back up to factory location**

WHEEL WELLS-

1. You may cut wheel wells for tire clearance. Fenders may be bolted back together with 5 -3/8" bolts or less with 1.25" diameter washers.
2. No rolling your fenders and welding them. If you wrap or fold your fenders around the front of the core support do not exceed 4 – 3/8" bolts with 1.25" washers to bolt back to the core support of the fender.

Hoods

1. Hoods must have a minimum 12x12 hole in it for fires can be bolted back together with 4 $\frac{3}{8}$ bolts with a standard nut and washer
2. hoods must remain open for tech if you come threw tech with it chained or wired down we will not inspect your car
3. hoods may be chained or wired in 8 spots you may weld a standard $\frac{5}{8}$ washer around holes to prevent ripping
4. you may use 3"x3" angle 6 inches long in 6 spots with 2 standard $\frac{1}{2}$ in bolt and washer must choose one or the other hood mounting options

FRONT CORE SUPPORT

1. Cannot be moved back from its factory location. It must stay BOLTED to the fenders the same way that it came factory.
2. The front two core support mounts may be changed to 1in thread rod and can be ran through the hood but will count as two of your tie down spots and can use no washers bigger than 4x4 $\frac{1}{4}$ plate or 5in round
3. spacers for coresupport may only be 2x2 tubing and can not be welded to frame or core support and must remain under core support
4. Nothing may be ran from core support spacer to bumper
5. All thread allowed thru core support is 1in max

Front and rear window openings

- You may have two front window bars
 - 2x2 max or 3in wide plate can run from halo to dash bar or cowl panel/ bottom of windshield
 - May be no closer than 12 inches together
 - If bar/plate is ran from halo to dash it will be considered part of cage and will need to remain 5 inches away from fire wall
 - If running to cowl panel it may not be more than 4 inches from bottom of windshield opening
 - May only have 2 attachment points 4 inches long on roof
5. In the rear window you may run 1 double strand of 9 wire from roof to speaker deck or may use $\frac{3}{8}$ chain may only be bolted all links must be free floating
 - If running a wagon no rear window bar permitted

6. If you cut out the center of your firewall you are permitted to cap the ends may not touch dash bar
7. Sun roofs must be covered
8. Fixing of sheet metal is limited to doors, roof, floor pans with in the driver's compartment
9. All sheet metals repairs may be done with metal no thicker than $\frac{1}{8}$ material and can only overlap 1 inch and can only be stitched welded back
10. No sheeting of quarters or fenders of cars

Cage

1. A 4 point cage and halo bar is highly recommend but is optional
 - Cage size may not exceed 2 x 6 $\frac{1}{4}$ or 4 inches in diameter
2. Cage can not be in the doors
3. All cage material must be 5 inches off floor no exceptions
4. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
 - Side bars must be 62 inches long and must also remain 5 inches away from fire wall and 5 inches from floor
5. May have a center bar must be 5in off all parts of the floor sheet metal
6. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it may be connected to the roof in two spots
 - Attachment points may be 2x2 $\frac{1}{4}$ 6 inch long angle with a $\frac{1}{2}$ bolt with a standard washer and nut only
7. You can have guessests in corners of the cage
8. 4 inch long max and 1/4 inch material

Gas tank protector

1. You will be allowed a 32in wide tank proctor
 - It may touch package tray but can not attach in anyway
 - If your car does not have a package tray you must keep your tank protector in front of rear axle
 - You are allowed to build an upper halo around your gas tank protector but can be no higher than 3 inches above tank
 - You may have bars running from tank protector to halo bar

Down bars

1. You may weld two down bars total one preside from the cage to the frame vertically to the floor to protect batteries and your feet. And must follow the following
 - These down bars must be mounted at front interior door seam
 - These bars cannot not exceed 2"x2 $\frac{1}{4}$

Front suspension

1. No aftermarket or modified spindles allowed must be a **factory car** spindle that is permitted to run this class
 - No aftermarket hubs must be oem you may turn the factory rotor down only
 - No bracing of spindles
2. No aftermarket springs must be factory car springs permitted to run this class

3. No aftermarket ball joints oem only store bought joints
 - If its a weld in in ball joint ring can only be ½ in bigger than ball joint itself
4. Arms must be for a car permitted in this class
 - A arms must remain factory origin and not contoured to the frame
5. You may lock front suspension by welding a 2x4¼ strap to front and rear side of a arm
 - No extra welds permitted other then the 2x4x1/4 strap all other welds will removed
 - Strap may not extend no more than 2 inches away from a arm
 - Nothing can be welded from lower a arm to frame
6. Cars with new style wishbone a arms may switch to older style
 - May run any style a arm that matches vehicles that permitted for this class
 - but must bolt to frame/brackets with no modifications allowed to brackets except cutting to remove metal but not be allowed to add back
 - Nothing can be between the a arm brackets if switching to older a arms
7. No removing of the shock cups on newer fords
8. Strut spacers are allowed but must be bolted no welding permitted
9. 03 and newer may run 80 ford spindles only all other suspension parts must remain the OEM part that come with the 03 and newer ford,mercury,lincolns.

Rear ends & rear suspension

1. Use the rear end of choice but must be no more than 8 lugs.
2. Welded or Posi-track highly recommended.
3. Back braces and axle savers are welcome
 - May only attach to the factory locations on frame
4. May run aftermarket rear control arms but must be with in following guidelines
 - Can not be bigger than 2x2 tube
 - Must have some type of bushing or pivot point
5. You may brace factory control arms with ¼ material
6. No aftermarket springs must be factory car springs permitted to run this class
7. Coils may be wired to rear end only
8. Factory leaf spring cars only can not altair in anyway may use 6 aftermarket clamps (3 per side) 3in long 2in wide and 5/16 bolt max
 - The main leaf must be the top spring in the spring pack
 - Leafs must be mounted as factory intended
 - Leafs must have factory stagger
 - Leafs must be same size and thickness that your vehicle was designed to have
9. No coil to leaf conversions
10. You may set your rear height by chaining it down
 - chains can not be welded and can only wrap around frame in one location on each side max ¾ chain but remember your bumper height restrictions
 - Front bumper height is 22 inches to bottom of the bumper
 - Rear bumper height is 15 inches to bottom of the bumper/frame at mounting area
 - All cars will meet bumper height requirements by our inspection area and all cars fresh or pre ran will meet requirement

shocks

- All thread shocks permitted in front and rear of vehicle
- Nuts and washers must be free floating max washer size is 3x3 ¼
- No washers or nuts permitted on inside of spring pockets
- No spring spacers allowed on top of springs inside the frame in front and rear of vehicle

Watts conversion

1. Watts Conversions are allowed but all brackets must be only large enough to hold a stock style sized control arm and not gusseted.
 - Control arms must be mounted in factory location and not shortened/moved to reinforce the car (Bottom control arm mounts cannot attach to the package tray).
 - All factory brackets must be completely cut off. Lower Bracket: 7"x4 ½"x1/4" to frame. Top Bracket: 11"x4 ½"x1/4" in factory location.
 - Nothing on the top side. May use (4)-1/2" bolts plus the center bolt to mount the bracket. Non-wat cars cannot change their mounts.
 - Can not bolt thru sheet metal or tie into cage
 - If doing a watts conversion, you have to do the full conversion, you have to move all the control arms and shocks like 97 and older FOMOCO cars

Steering

- Steering column may be changed to an aftermarket
- aftermarket or modified tie rods will be allowed
 - May use hemi joints with ½ bolt max
- 03 and newer fords,mercurys,and lincolns must use the factory rack and pinion oem only no truck racks and no hydro steering
- Must run factory steering box for car that is legal in this class
- Adapter plates are permitted and cannot reinforce the car.
- Adapter plate can be ½" bigger than the steering box housing and ½" thick, it may not be welded to the frame.
- The adapter plate can only mount to frame where the steering box mounted to the frame factor

Tires

1. Any tire and wheel combo permitted
2. Must have started as a factory rim
3. May run bead locks, lip proctors, full centers, valve stem protectors

motor/trans

1. May run any motor and transmission combination
2. Oil pans may be plated but must conform to oil pan and may be no bigger than bottom of pan itself
3. Lower cradles with front plates are allowed
 - Lower cradles may not go past headers/back of head
 - If your cradle has a pulley protector swap bar must be completely removed
 - Pulley proctors may not come into contact with any frame/crossmember on any vehicle

- No fix it plates are allowed to attach cradle to frame
4. No distributor protectors transmission braces coil pack protectors no mid plates no protectors in general
 5. If not running a lower Cradle you will be allowed 4 motor chains $\frac{3}{8}$ links two links may be welded to frame all other links are to be free floating
 6. 03 and newer Engine Mounting rule you may use a cradle like grey area or budde cradle or a smith metal works cradle. Still must use a stock style rubber mount. The cradles are allowed to attach with one bolt through each aluminum tower or big bolts on top of the frame one or the other. no other attachment points and must remain $\frac{1}{2}$ inch off the side rail. Repair plates may not be used to tie cradles into the rails call for any questions

Motor mounts

1. must have some type rubber or poly bushing can be aftermarket
2. Motor mount pad may not exceed 6"x6"
3. Mounting pads may not exceed 6"x6"x1/4" for cars needing to move motor forward or backwards

Transmission

1. Stock transmission cases only
 - You will be allowed an aftermarket aluminum bell
 - If you do not have an aftermarket bell you may weld 2- 2 inch wide $\frac{1}{4}$ aluminum strips on your factory bell
 - Strap/weld must remain in front of transmission pump
 - Tails must remain factory
2. Transmission pans may be plated but must conform to the pan and at no point be bigger than outer edge

TRANSMISSION CROSSMEMBER

1. You must run the transmission cross member in the stock location on trans
 - You can weld 2" angle iron no thicker than $\frac{1}{4}$ ", no longer than 8" to the side of the frame to support the cross member. You must remove the stock mount if you run the angle iron.
 - You may use any factory crossmember or it can be replaced with up to a 2" x 2" piece of steel.
 - The transmission cross member must be one piece and must be straight from side to side (No arched cross members).
 - The transmission cross member is the only method which the transmission may be tied in
 - Cars that have frame extensions need to stay one inch off the cross member. The transmission crossmember and supporting angle iron cannot tie into or run under the frame extensions on the Cadillac. Frame extensions must be 1" clearance from the front,top,side, and bottom of the crossmember.

Full tanks

1. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure
2. Must be secured and safe if we deem any part of fuel system is unsafe you will fix issues until it's deemed safe

3. **(we all have families that need us this rule is the most important and will be enforced no matter the outcome)**

Aftermarket parts

4. Transmission or oil coolers are permitted but must be mounted in drivers compartment and must use appropriate lines (hydraulic hoses are highly recommended)
5. You may run aftermarket shifter
6. Aftermarket pedals may be ran
7. Sliders permitted
8. Headers will be allowed
9. Simple radiator line loop is allowed no home made radiators allowed
 - Radiator may only be mounted in engine compartment in the core support
 - You will be allowed two spots to mount

Tech and approval question call matthew kingree 540 335 6439

Stock Modified

General rules/ car preparations

1. Any year car permitted except for the following limos ,checker cabs, trucks, suvs no imperials or chrysler products with imperial subs c
2. Cars Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show all wagons must remove roof racks and decking
3. All glass must be removed and swept clean
4. Original full tanks must be removed and placed in back seat area
5. All batteries must be moved in the drivers compartment (2 battery maximum)
6. Car must have a seat belt and working brakes at all times
7. You will have two times threw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
8. **Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech**
9. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want)
10. All judge's decision are final
11. We reserve the right to drill,scope,unbolt anything we feel could potentially be hiding something
12. Pre ran cars must follow these rules and change what needs to be changed we will not change the rules to fit your car you must change your car to fit our rules

Frames

1. Frames must be 100 percent stock absolutely no welding anywhere will be permitted unless otherwise stated
2. Frames must remain factory length no shortening of front or rear
3. No seam welding even where factory missed
4. All cars will be allowed 2 3x3 1/8 plates only
5. No tilting cold bending or any kind of frame work
6. You may notch or dimple cars
7. Sway bar must be 100% factory mounts

Bumpers

1. Any factory loaded seam welded automobile bumper
 - we will be allowing a smith metal works or similar bumpers
 - 4x4x1/4 tube must remain flat ends must be capped and may not stick out no further than outside edge of tire
 - No pointy bumpers/ramp bumpers on rear of car
 - You may run factory shock or bracket that is for the car your running
 - Shock or bracket must be the same way factory intended it and in factory location of frame
 - Bumpers may be welded to shock/bracket

- Brackets or shocks that are factory bolted must remain that way with no weld added if its a weld on bracket or shock we must see factory welds
- No plug welding of factory brackets or shocks
- If you choose to weld the bumper straight to the frame all shocks and brackets must be removed
- You may wire your bumpers in two spots must be to sheet metal only with 9 wire only

Body

1. No body modifications must be stock unless otherwise stated
2. No changing of body mounts must remain factory zero modifications
3. Doors may be welded with a total of 4 plates 3x3x1/4 per door vertical seam
 - You will be allowed a inner or outer door plate on drivers side only this is for drivers protection (may have both)
 - No thicker than 1/4 inch and can only go 3 inches of each door seam
4. If not welded may be chained or wired 10 spots per door sheet metal to sheet metal only
5. Trunks must remain factory may be wired or chained in 6 spots sheet metal to sheet metal only
6. Hoods must have a minimum 12x12 hole in it for fires
7. Hoods may be wired or chain 8 spots total sheet metal to sheet metal only
8. You may wire your bumpers in two spots must be to sheet metal only with #9 wire double strand
9. You are allowed to crease your car but quarters must remain factory height no folding of the quarters over
 - If car is pre ran you must attempt to bring quarters in the upright position
10. You may have a front window bar 3in wide plate can only be mounted 6 inches on roof firewall may not touch roll bar
11. In the rear window you may run 1 double strand of 9 wire from roof to speaker deck or may use 3/8 chain may only be bolted all links must be free floating
12. No rear window bars on wagons

Cage

1. A 4 point cage and halo bar is optional but is highly recommend
2. Cage can not be in the doors
3. Cage sizes will be 4x4 or 2x6
4. All cage components must be 5 inches off floor
5. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
 - Side bars 62in max and must remain 5 inches off firewall
6. May have a center bar must be 5in off all parts of the floor sheet metal
7. NO DOWN BARS will be allowed no not even the ones that only weld to the sheet metal
8. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it may not be connected to the roof
9. No gas tank protectors

- If your gas tank needs to be on a holder it can not be any bigger than 32 inches wide and must be 5 inches off all sheet metal no you may not remove sheet metal
- 10. You can have guessests in corners of the cage 4 inches long max
- 11. made out of 1/4inch plate
- 12. If your cage is determined unsafe you will be required to change or remove complete to prevent injury to yourself or others

Suspension

1. No aftermarket or modified spindles allowed must be a factory car spindle
2. No aftermarket hubs
3. No aftermarket ball joints oem only
 - Must be factory for the car you are running
4. Must have working suspension front and rear

Rear

1. Must run factory rear to your car no switching makes or models
2. All control arms must be factory
3. No watts conversion kits
4. Coils may be wired to rear end only
5. Factory leaf springs only can not altair in anyway may use 4 aftermarket clamps (2 per side) 3in long 2in wide and 5/16 bolt max
6. No coil to leaf conversions You may set your rear height by chaining it down chains can not be welded and can only wrap around frame in one location on each side max $\frac{3}{8}$ chain
7. Pinion break are allowed but must remain on factory rears

Steering

1. Steering columns
 - Aftermarket columns will be permitted
 - No aftermarket or modified tie rods must remain factory

Tires

1. Any tire may be used must be no bigger than 16 inches
2. Must use a factory rim and tire allowed
3. May use a small weld in center (7inch or smaller)
4. No bead locks solid rims solid tires

motor/trans

1. Must run factory motor to the car you are running
 - You may switch fuel injected or throttle body cars to carbureted must be done with oem parts
2. You can not put a newer motor in an older vehicle or vice versa (example no LS motors in an older gm)
3. Transmission must be stock oem case with no metal added for bracing

4. no switching of makes ford to ford chevy to chevy
5. Motor mounts must be factory oem
6. May have two engine chains one on each side of the motor may only weld to engine crossmember or side rails only one link may be weld all others must be free floating $\frac{3}{8}$ chain max
7. Transmission cross members must be factory to car and mounted in factory location with a oem mount no chains allowed trans
8. You may run aftermarket pedals and shifter if you choose to
9. Transmission lines must be looped no trans coolers required
10. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure (we all have families that need us this rule is the most important and will be enforced no matter the outcome)
11. No sliders
12. Headers allowed
13. Battery boxes highly recommended jeffy fab farm or equivalent

Compact truck,suv, and van

General rules/ car preparations

1. Any factory 2 or 4 wheel drive truck,suv, and van with 4,6 cylinder
2. No full size vans no ½ ton or ¾ ton trucks no suburbans or full size broncos or full size blazers or the 80s dodge raiders ram chargers etc
3. Motor must be same make (ford to ford chevy to chevy) etc
4. If 4 wheel drive one of the drive shafts need to be removed or axles
5. Cars Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show
6. All glass must be removed and swept clean
7. Original full tanks must be removed and placed in back seat area
8. All batteries must be moved in the drivers compartment (2 battery maximum)
9. Car must have a seat belt and working brakes at all times
10. You will have two times threw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
11. Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech
12. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want)
13. All judge's decision are final
14. We reserve the right to drill,scope,unbolt anything we feel could potentially be hiding something
15. Pre ran cars must follow these rules and change what needs to be changed we will not change the rules to fit your car you must change your car to fit our rules

Frame

1. Frames must be stock no welding unless otherwise stated
2. No seams may be welded
3. Frames can be shortened to core support
4. All frame holes must remain open
5. 4 fix it plates on pre ran or fresh vehicles (4x4 ¼ square plates)

Body

1. All body bolts must remain factory only bolts allowed to be changed is the front core support and can be ¾ in all thread and may run thru hood but must have minimum 1 inch gap
2. Drivers door may be welded solid all other doors can be welded with the 5 on 5 method (put a plate skip 5 inches put other plate) or may use chain or 9 wire
3. Tops of doors may not be welded
4. Bed sides on trucks need to stay at factory height
5. Bed sides may be welded to cab in 2 locations 3x3x1/4

6. Tailgates may be welded with total of 6 plates or may use 8 spots of chain and 9 wire sheet metal to sheet metal must pick one way not both
7. Hoods may be bolted down with a total of 6 spots two of the spots being the threaded rod running thru core support the other two spots may be 2x2 angle 4 inch long with $\frac{3}{8}$ bolt max or you may have chain or 9 wire
8. All hoods must have a 12x12 hole for fires may be bolted back with 4 $\frac{3}{8}$ bolts

Cage

1. A 4 point cage and halo bar is highly recommend
2. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
3. May have a center bar must be 5in off all parts of the floor sheet metal
4. NO DOWN BARS will be allowed no not even the ones that only weld to the sheet metal (only a 2x2 $\frac{1}{4}$ down bar may be ran on drivers door must be centered in sidebar and may only weld to sheet metal only)
5. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it also may be connected to the roof in two locations only with 3 in long 2x2 angel with a $\frac{1}{2}$ in bolt maximum
6. You will be allowed a gas tank protector 32in wide maximum it will be allowed to touch the package tray only can be bolted or welded if you build a halo over the back half of your tank it can not be attached to roof
7. You can have guessests in corners of the cage

Suspension

1. Must be all factory components no aftermarket spindles or ball joints must be all OEM parts if using a weld in style ball joint it must have limited fabrication done (don't get crazy with a welder and you won't have to get crazy w cutting)
2. No aftermarket springs
3. No ball joint protector
4. May use aftermarket steering columns
5. No Aftermarket tie rods will be allowed may brace factory ones only
6. You may lock front suspension you may weld strut or use a 2x4 $\frac{1}{4}$ plate front and back side of a arm
7. You may run 1in all thread in place of the shock 3in washer max non welded no nuts or washers allowed inside of coil pocket one nut and washer on top and same on bottom
8. Trucks Must use factory rears and can not be attached to frame other then where factory intended you may have solid suspension in the rear and May use all thread shocks in rear car does not have to bounce
9. no coil to leaf conversion
10. Factory leaf spring vehicles with factory leafs may have 4 total clamps on each leaf (2in wide 4 in long 5/16 bolt do not put tape around leafs)
11. You may wire or weld your coil springs to rear do not weld springs to frame in anyway
12. Any tires will be permitted black and round

13. You may have full center rims and a valve stem protector, lip guard protector can only be 1in wide will be allowed bead locks will be permitted

Bumpers

1. Any car bumpers will be allowed may be loaded you may choose to fabricate your own bumper must be in following guidelines 8x8 tube u may have a point must expand over 32 in of front and can only stick out 4 in from front edge of the tube (so from the point to back of bumper has to be 12 inches in total length)
2. Factory replica bumpers will be allowed
3. Rear bumpers must remain factory you may seam weld bumpers but no metal may be added (smw or dec or a standard 4x4 1/4 tube may be used bumpers may be used)
4. Front Bumpers may be welded on but may only use one of the following options. Option number 1 use the factory bracket that came with your car option number 2 you may hard nose your bumper and run a 4inch wide $\frac{3}{8}$ flat plate (notice flat no teepee plates angel plates flat only) 12in long bumper shock welded to the side of the frame facing towards tire and can only have $\frac{3}{8}$ bead of weld around outside surface (12in means 12in from back of the bumper so anything pass that 12 in mark will be completely removed and remember your 4x4 $\frac{1}{4}$ plate have to remain 1 in away from bumper shock)
5. Rear bumpers may be welded on with a and may have a 12in rear bumper bracket
6. If using factory shock it can only be welded or bolted with in the first 4 inches
7. Front bumper may be no higher than 22in to bottom of bumper and rear bumper may be no lower than 14in
8. You may 9 wire two spots from core support to front bumper may not go around hood core support only 2 strands maximum no 9 wire from trunk to rear bumper

Motor and trans

1. 4,6 and 8 cylinders must be same make and model ford to ford chevy to chevy etc
2. Must run same motor that comes in your model you can not put a v8 in a 4 or 6 cylinder body
3. Motor mounts may be changed to 2x2 tube max and must mount as factory intended
4. no distributor protectors no coil or engine cradles in general
5. No trans braces will be allowed
6. Trans mounts must be factory you may chain trans around the mount
7. Trans and oil coolers are permitted but must be mounted in drivers compartment and must use appropriate lines (hydraulic hoses are highly recommended)
8. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure (we all have families that need us this rule is the most important and will be enforced no matter the outcome)
9. If tank is in front of rear axle you may leave it there and must have a skid plate
10. All fuel lines need to be doubled clamped
11. May have two engine chains one on each side of the motor may only weld to engine crossmember not to side rails only one link may be weld all others must be free floating $\frac{3}{8}$ chain max
12. Carb conversions will be allowed

Full Size Truck General rules/ car preparations

1. Any factory 2 or 4 wheel drive truck,suv, and van
2. Vehicles Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show
3. All glass must be removed and swept clean
4. Original full tanks must be removed and placed in back seat area
5. All batteries must be moved in the drivers compartment (2 battery maximum)
6. Car must have a seat belt and working brakes at all times
7. You will have two times threw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
8. Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech
9. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want)
10. All judge's decision are final

Frame

1. Frames must be stock no welding unless otherwise stated
2. seams may be welded
3. Frames can be shortened to core support
4. All frame holes must remain open
5. 4 fix it plates on fresh vehicles (4x4 ¼ square plates)
6. 8 fix it plates on preran vehicles (4x4 ¼ square plates)

Body

1. All body bolts may be changed to 5/8 bolts
2. Drivers door may be welded solid all other doors can be welded with the 5 on 5 method (put a plate skip 5 inches put other plate) or may use chain or 9 wire
3. Tops of doors may be welded
4. Bed sides may be welded to cab
5. Tailgates may be welded with total of 6 plates or may use 8 spots of chain and 9 wire sheet metal to sheet metal must pick one way not both
6. Hoods may be bolted down with a total of 6 spots two of the spots being the threaded rod running threw core support the other two spots may be 2x2 angle 4 inch long with 3/8 bolt max or you may have chain or 9 wire
7. All hoods must have a 12x12 hole for fires may be bolted back with 4 3/8 bolts

Cage

1. A 4 point cage and halo bar is highly recommend but optional

2. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
3. May have a center bar must be 5in off all parts of the floor sheet metal
4. DOWN BARS will be allowed must be mounted in cab and may be to frame only
5. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it also may be connected to the roof in two locations only with 3 in long 2x2 angel with a ½ in bolt maximum
6. You will be allowed a gas tank protector 32in wide maximum it will be allowed to touch the package tray only can be bolted or welded if you build a halo over the back half of your tank it can not be attached to roof
7. You can have guessests in corners of the cage

Suspension

1. Must be all factory components no aftermarket spindles or ball joints must be all OEM parts if using a weld in style ball joint it must have limited fabrication done No aftermarket springs
2. No ball joint protector
3. May use aftermarket steering columns
4. No Aftermarket tie rods will be allowed may brace factory ones only
5. You may lock front suspension you may weld strut or use a 2x4 ¼ plate front and back side of a arm
6. You may run 1in all thread in place of the shock 3in washer max non welded no nuts or washers allowed inside of coil pocket one nut and washer on top and same on bottom
7. Trucks Must use factory rears and can not be attached to frame other then where factory intended you may have solid suspension in the rear and May use all thread shocks in rear car does not have to bounce
8. no coil to leaf conversion
9. Factory leaf spring vehicles with factory leafs may have 4 total clamps on each leaf (2in wide 4 in long 5/16 bolt do not put tape around leafs)
10. You may wire or weld your coil springs to rear do not weld springs to frame in anyway
11. Any tires will be permitted black and round
12. You may have full center rims and a valve stem protector, lip guard protector can only be 1in wide will be allowed bead locks will be permitted

Bumpers

1. Any car bumpers will be allowed may be loaded you may choose to fabricate your own bumper must be in following guidelines 8x8 tube u may have a point must expand over 32 in of front and can only stick out 4 in from front edge of the tube (so from the point to back of bumper has to be 12 inches in total length)
2. Factory replica bumpers will be allowed
3. Rear bumpers must remain factory you may seam weld bumpers but no metal may be added (smw or dec or a standard 4x4 1/4 tube may be used bumpers may be used)

4. Front Bumpers may be welded on but may only use one of the following options. Option number 1 use the factory bracket that came with your car option number 2 you may hard nose your bumper and run a 4inch wide $\frac{3}{8}$ flat plate (notice flat no teepee plates angel plates flat only) 12in long bumper shock welded to the side of the frame facing towards tire and can only have $\frac{3}{8}$ bead of weld around outside surface (12in means 12in from back of the bumper so anything pass that 12 in mark will be completely removed and remember your 4x4 $\frac{1}{4}$ plate have to remain 1 in away from bumper shock)
5. Rear bumpers may be welded on with a and may have a 12in rear bumper bracket
6. If using factory shock it can only be welded or bolted with in the first 4 inches
7. Front bumper may be no higher than 22in to bottom of bumper and rear bumper may be no lower than 14in
8. You may 9 wire two spots from core support to front bumper may not go around hood core support only 2 strands maximum no 9 wire from trunk to rear bumper

Motor and trans

1. Any motor or transmission combo
2. Motor mounts may be changed to any factory or rubber style mount
3. no distributor protectors no coil protectors
4. Lower engine cradles permitted
5. No trans braces will be allowed
6. Trans mounts must be factory you may chain trans around the mount
7. Trans and oil coolers are permitted but must be mounted in drivers compartment and must use appropriate lines (hydraulic hoses are highly recommended)
8. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure (we all have families that need us this rule is the most important and will be enforced no matter the outcome)
9. If tank is in front of rear axle you may leave it there and must have a skid plate
10. All fuel lines need to be doubled clamped
11. May have two engine chains one on each side of the motor may only weld to engine crossmember not to side rails only one link may be weld all others must be free floating $\frac{3}{8}$ chain max
12. Carb conversions will be allowed

2024 youth compacts

General rules/ car preparations

1. Any year car permitted front wheel drive cars only within 110 inch wheelbase
2. Cars Must be complete stripped clean no trim interior or any other flammable materials must be removed prior to the show all wagons must remove roof racks and decking
3. All glass must be removed and swept clean
4. All batteries must be moved in the drivers compartment (2 battery maximum)
5. Car must have a seat belt and working brakes at all times
6. You will have two times throw tech if on your second attempt you did not meet satisfaction to what the inspectors wanted you will be loaded and no refund will be issued (as our job of inspections we will make sure it is clear and understandable of what we want done so there shouldn't be any questions or miss understanding)
7. **Drivers only in tech no one else is allowed (we will give you a piece of paper with everything written down for you to take back with you to show your crew) must have paper with you for re tech**
8. All rules are to the interpretation to the officials (if unsure of a rules call or text to get clarification so you understand what we want)
9. All judge's decision are final
10. We reserve the right to drill,scope,unbolt anything we feel could potentially be hiding something
11. Pre ran cars must follow these rules and change what needs to be changed we will not change the rules to fit your car you must change your car to fit our rules

Frames

1. Frames must be 100 percent stock absolutely no welding anywhere will be permitted unless otherwise stated
2. No seam welding even where factory missed
 - If found you will cut the center of weld out with a grinder or torch
3. You may notch or dimple cars in one location
4. UNIBODY CARS STILL HAVE FRAME RAILS, FOLLOW THE FRAME BUILDING RULES.
5. No painting of frames
 - If found you will be required to remove
 - Over spray is considered paint and will be removed also
 - No fresh undercoating
6. If frame is rusted we must have proof of rust and must be approved

Shorting of frames

1. May shorten frame to front edge of Core support
2. No shorting of rear of vehicles

Repair/fresh plates/9 wire

1. If car is fresh/pre ran you are allowed 4- 4x4" ¼" square plates (2 per rail)
 - Square or parallelogram plates
 - Must have a 1 inch gap between welds
 - Welds/plate Must remain 2 inches away from bumper shock/ bracket

- May have 8 spots of double strand 9 wire from sheet metal to sub/uni body May not connect or go around any part of cage
- Plates must be external
- Must be painted orange for easy identification
- Plates are not allowed to tie subframe to uni bodys or k frames to uni bodys
- No 9 wire or chain may be ran from subframe to k frame

Bumpers

1. Any factory loaded seam welded automobile bumper
2. **Use bumper rules for front and rear of car**
 - we will be allowing a smith metal works or similar bumpers
 - Home made bumpers not to exceed 6x6 tube may have a point must not be no more than 4in away from front face of bumper and must expand 32 inches across the front
 - Rear bumpers must be a minimum of 5 inches on back surface
 - Replicated bumpers will be allowed except pointy replicas
 - **No pointy or slanted bumpers on rear of any car**

Bumper mounting

1. You will be allowed a 4 inch wide by 6 inch long bumper bracket (4"x6"x 3/8")
 - Plate can only be on one side of the frame not all 4
 - May contour or remain straight
 - Must touch front bumper and anything past 6 inches will be removed factory or not
 - If you choose to run a factory shock or bracket anything pass the 6 inches will be removed
 - If using the plate options you must remove factory shock/ bracket
2. Bumper brackets and shocks must be factory to car you are running and bumper shocks must be in the factory location
3. May use a 6"x6" 1/4 plate welded to end of frame to make a flat mounting surface must be welded in between the fame and bumper and remain the 6"x6" no folding over plate on to frame
4. Bumpers may be welded on to the end of the frame no sliding bumper over or inside of end of the frame or subframe rails
5. If unable to weld your bumper on you may wire, chain, and bolt your bumper on and may leave the shock this is for the cars that bumper was not welded on
6. You are allowed two spots of double strand 9 wire from bumper to sheet metal only must follow the following
 - On the front bumper 9 wire may only go around core support may not be wrapped through hood or around front all thread mounts
 - Rear bumper 9 wire may only go from bumper to trunk lid must only be to sheet metal

Body

1. No body modifications must be stock unless otherwise stated

2. No changing of body mounts must remain factory zero modifications
3. Creasing is allowed but limited to front fenders and rear quarters

Doors

1. Drivers door and front passengers door may be welded solid and all other doors may be welded with a total of 6 plates 3x5x1/4
 - You will be allowed a inner or outer door plate on drivers door and passengers door only this is for drivers protection
 - No thicker than 1/4 inch and can only go 3 inches of each door seam
2. If not welded may be chained or wired 8 spots per door
3. you may weld a standard 5/8 washer around holes to prevent ripping
4. Top of doors may be beat down but may not be welded,bolted, or screwed back in place

trunks/tailgates

1. Rear quarters must remain factory height
2. Trunks must remain factory and above rain channels you may do a simple tuck but can not attach to the floor in any way
3. Trunks can be may be chained or wired,welded must pick one of the three options
 - If wired may have 10 spots you may not exceed over two strands of 9 wire thru each spot a 5/8 standard store bought washer may be welded around whole to prevent ripping
 - If chained you may do 8 spots 3/8 links and must remain free floating a 5/8 standard store bought washer may be welded around whole to prevent ripping
 - If welded you may do 6 spots 3x5x1/4 plate may be used

Hoods

1. Hoods must have a minimum 12x12 hole in it for fires can be bolted back together with 4 3/8 bolts with a standard nut and washer
2. hoods must remain open for tech if you come threw tech with it chained or wired down we will not inspect your car
3. hoods may be chained, wired or bolted one of the three may be used
 - If chained or wired you may do 8 spots of wire or chain you may weld a standard 5/8 washer around holes to prevent ripping
 - If bolted you may use 6 spots and you may use 2x2 angle 2 inches long in 6 spots with a standard 1/2 bolt and washer

Window bars

1. You may have one front and rear window bar can only attach to first 6 inches of roof and first 6 inches of cowl panel or trunk lid closest to window
 - If its square tube nothing bigger than 2x2 1/4 pipe
 - 3in wide 3/8 stock bar
 - Chain
 - Or 9 wire
 - One of the following not all of them
 - No rear window bars on wagons

Cage

1. A 4 point cage and halo bar is highly recommend but is optional
 - Cage size may not exceed 2 x 6 ¼ or 4 inches in diameter
2. Cage can not be in the doors
3. All cage material must be 5 inches off floor no exceptions
4. your dash bar must be 5 in off the firewall and 5 in off the trans tunnel your rear seat bar may not be any farther back then where the rear kick panel meets the floor (where the front of the back seat would be located)
 - Side bars must be 62 inches long and must also remain 5 inches away from fire wall and 5 inches from floor
5. May have a center bar must be 5in off all parts of the floor sheet metal
6. Halo bars are allowed must be straight up and down and connect to rear seat or side bars it may be connected to the roof in two spots
 - Attachment points may be 2x2 ¼ 6 inch long angle with a ½ bolt with a standard washer and nut only
7. You can have guessests in corners of the cage
8. 4 inch long max and 1/4 inch material

Gas tank protector

1. You will be allowed a 32in wide tank proctor
 - It can not attach to any sheet metal and must stay in front of rear axle
 - You are allowed to build an upper halo around your gas tank protector but can be no higher than 3 inches above tank
 - You may have bars running from tank protector to halo bar
 - **If your tank is under your car you may not have a tank protector**

suspension

1. Must remain stock absolutely no aftermarket or modified parts 100% stock
2. Only aftermarket parts your allowed is spring spacers or the strut risers
3. Cars must have suspension bounce
4. No aftermarket or modified tie rods must remain factory
5. Steering column may be changed to an aftermarket
6. All control arms must be stock and no modifications allowed and must be in in factory location of the car you are running
7. No chaining of the rear to set the height

Tires

1. Any tire may be used must be no bigger than 16 inches
2. Must use a factory rim
3. No bead protectors no lip protectors no full centers no valve stem protectors
4. You will be allowed a small multi lug center (7in)
5. May run a rubber flap on outside of the wheel

motor/trans

1. Motor and trans must be factory to make and model no switching makes (ford to ford chevy to chevy Toyota to Toyota)

2. You may run an aftermarket motor mounts on front of engine only 2x2 max size
 - Toyota products may change the front motor mount running to the k frame must bolt back as factory intended no welding allowed
 - Gm products may change the upper two mounts must bolt in to the factory brackets on both motor and core support
 - Honda products may change the front mount also must be done as factory attend
3. No engine cradles distributor protectors trans braces coil pack protectors no protectors in general must all be oem
4. Trans must be factory to car and mounted in factory location
5. Trans coolers are permitted but must be mounted in drivers compartment and must use appropriate lines (hydraulic hoses are highly recommended)
6. You may run aftermarket shifter
7. If tank is under the car and in front of the rear axle you may leave it there but must have metal skid plate
8. Headers will be allowed
9. Carb conversions are allowed

Full tanks

1. Any metal fuel cells permitted or boat tanks if its a plastic tank it must be in some type of metal structure
2. Must be secured and safe if we deem any part of fuel system is unsafe you will fix issues until it's deemed safe
3. **(we all have families that need us this rule is the most important and will be enforced no matter the outcome)**
4. If tank is in front of rear axle it may be left there but must have a skid plate

Aftermarket parts premitied

1. Headers
2. Shifters
3. Pedal combos
4. Steering columns
5. Fuel cells

Nothing else is permitted unless approved by either jesse bly or matthew kingree

For all rule questions please contact jesse bly at (540) 335-0723